
Revision nr.3 Dated 7/7/2020 Printed on 7/7/2020 Page n. 1 / 10 Replaced revision:2 (Dated 4/24/2018)

MI554AU-0 - Tartaric Acid Reagent A (test vial)

## Safety Data Sheet

According to U.S.A. Federal Hazcom 2012 and Canadian HPR - WHMIS 2015



Classification and Hazard Statement Serious eye damage, category 1 Skin irritation, category 2

Hazard pictograms:



Causes serious eye damage. Causes skin irritation.

Signal words:

Danger

Wear protective gloves / eye protection / face protection.

Hazard statements:	
H318	Causes serious eye damage.
H315	Causes skin irritation.

Precautionary statements: Prevention: P280 Response: P302+P352 P305+P351+P338

IF ON SKIN: Wash with plenty of water and soap. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. ΕN

MI554AU-0 - Tartaric Acid Reagent A (test vial)

## 2. Hazards identification ... / >>

P310 Storage:	Immediately call a POISON CENTER or doctor.

Disposal:

## 2.2. Other hazards

Information not available

## 3. Composition/information on ingredients

#### 3.2. Mixtures

Identification	x = Co	onc. %	Classification:
ACETIC ACID	1		
CAS	64-19-7 1	≤x< 5	Flammable liquid, category 3 H226, Substance or mixture corrosive to metals category 1 H290, Skin corrosion, category 1A H314, Serious eye damage, category 1 H318
EC	200-580-7		
INDEX	607-002-00-6		

The full wording of hazard (H) phrases is given in section 16 of the sheet.

## 4. First-aid measures

### 4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

#### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

ACETIC ACID

ACETIC ACID 100%: Irritation and corrosion, bronchitis, Shortness of breath, gastric spasms, Nausea, Vomiting, Circulatory collapse, shock, Risk of corneal clouding. Risk of blindness!.

### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

## 5. Fire-fighting measures

## 5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray. UNSUITABLE EXTINGUISHING EQUIPMENT None in particular.

## 5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

## ACETIC ACID

ACETIC ACID 100%: Combustible. Vapours are heavier than air and may spread along floors. Forms explosive mixtures with air at elevated

## MI554AU-0 - Tartaric Acid Reagent A (test vial)

### 5. Fire-fighting measures ... / >>

temperatures. Development of hazardous combustion gases or vapours possible in the event of fire. Fire may cause evolution of: Acetic acid vapours.

### 5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations. SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

#### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

#### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

## 7. Handling and storage

#### 7.1. Precautions for safe handling

Ensure that there is an adequate earthing system for the equipment and personnel. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid leakage of the product into the environment.

## 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed. Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.

### 7.3. Specific end use(s)

Information not available

## 8. Exposure controls/personal protection

#### 8.1. Control parameters

Regulatory References:

USA USA USA	NIOSH-REL OSHA-PEL CAL/OSHA-PEL	NIOSH publication No. 2005-149, 3th printing, 2007. Occupational Exposure Limits - Limits for Air Contaminants TABLE Z-1-1910.1000. California Division of Occupational Safety and Health (Cal-OSHA) Permissible Exposure Limits (PELs).
EU	OEL EU TLV-ACGIH	Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC. ACGIH 2019

MI554AU-0 - Tartaric Acid Reagent A (test vial)

### ACETIC ACID

alue									
Country	TWA/8h		STEL/15	STEL/15min					
	mg/m3	ppm	mg/m3	ppm					
EU	25	10	50	20					
-		10		15					
USA	25	10							
USA	25	10	37 (C)	40 (C)					
USA	25	10	37	15					
	Country EU - USA USA	Country TWA/8h mg/m3 EU 25 - USA 25 USA 25	Country         TWA/8h           mg/m3         ppm           EU         25         10           -         10           USA         25         10           USA         25         10	Country         TWA/8h         STEL/15           mg/m3         ppm         mg/m3           EU         25         10         50           -         10         10           USA         25         10         37 (C)	Country         TWA/8h         STEL/15min           mg/m3         ppm         mg/m3         ppm           EU         25         10         50         20           -         10         15           USA         25         10         37 (C)         40 (C)	Country         TWA/8h         STEL/15min           mg/m3         ppm         mg/m3         ppm           EU         25         10         50         20           -         10         15           USA         25         10         37 (C)         40 (C)	Country         TWA/8h         STEL/15min           mg/m3         ppm         mg/m3         ppm           EU         25         10         50         20           -         10         15         USA         25         10           USA         25         10         37 (C)         40 (C)	Country         TWA/8h         STEL/15min           mg/m3         ppm         mg/m3         ppm           EU         25         10         50         20           -         10         15           USA         25         10         37 (C)         40 (C)	Country         TWA/8h         STEL/15min           mg/m3         ppm         mg/m3         ppm           EU         25         10         50         20           -         10         15           USA         25         10         37 (C)         40 (C)

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

#### ACETIC ACID

Methods for measurement of the workplace atmosphere have to correspond to the requirements of norms UNI EN 482 and UNI EN 689.

#### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must comply with current regulations. HAND PROTECTION

Protect hands with category III work gloves (OSHA 29 CFR 1910.138).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear. Wash body with soap and water after removing protective clothing. EYE PROTECTION

Wear airtight protective goggles (OSHA 29 CFR 1910.133).

**RESPIRATORY PROTECTION** 

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a NIOSH certified filter, whose class must be chosen according to the limit of use concentration (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus or external air-intake breathing apparatus. For a correct choice of respiratory protection device, see standard NIOSH 42 CFR 84, OSHA 29 CFR 1910.134.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

## 9. Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Properties	Value
Appearance	liquid
Colour	colourless
Odour	pungent
Odour threshold	Not available
pH	3.7
Melting point / freezing point	Not available
Initial boiling point	Not available
Boiling range	Not available
Flash point	Not applicable
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	1
Solubility	soluble in water
Partition coefficient: n-octanol/water	Not available

Information

MI554AU-0 - Tartaric Acid Reagent A (test vial)

 Auto-ignition temperature
 Not available

 Decomposition temperature
 Not available

 Viscosity
 Not available

 Explosive properties
 not applicable

 Oxidising properties
 not applicable

 9.2. Other information
 1,07 %

## 10. Stability and reactivity

## 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

ACETIC ACID

ACETIC ACID 100%: Vapour/air-mixtures are explosive at intense warming.

## 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

## 10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

## ACETIC ACID

ACETIC ACID 100%: Risk of explosion on contact with: chromium (IV) oxide, potassium permanganate, sodium peroxide, perchloric acid, phosphorus chloride, hydrogen peroxide. Can react dangerously with: alcohols, bromine pentafluoride, chlorosulphuric acid, dichromate-sulphuric acid, ethane diamine, ethylene glycol, potassium hydroxide, strong bases, sodium hydroxide, strong oxidising agent, nitric acid, ammonium nitrate, potassium tert-butoxide, oleum. Forms explosive mixtures with air.

## 10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

ACETIC ACID

ACETIC ACID 100%: Avoid exposure to sources of heat and naked flames.

## 10.5. Incompatible materials

ACETIC ACID

ACETIC ACID 100%: Carbonates, hydroxides, many oxides and phosphates. Oxidising substances and bases.

## 10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

## 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

## 11.1. Information on toxicological effects

## ACETIC ACID

ACETIC ACID 100% - Acute oral toxicity, Symptoms: If ingested, severe burns of the mouth and throat, as well as a danger of perforation of the oesophagus and the stomach., Nausea, Vomiting, Risk of aspiration upon vomiting., Pulmonary failure possible after aspiration of vomit - Acute inhalation toxicity, LCLO Rat: 39.95 mg/l, 4 h, Symptoms: mucosal irritations, Cough, Shortness of breath, Possible damages:, damage of respiratory tract, Pneumonia, bronchitis, Inhalation may lead to the formation of oedemas in the respiratory tract., Symptoms may be delayed - Skin irritation, Rabbit, Result: Causes burns - Eye irritation, Rabbit, Result: Causes serious eye damage. Risk of blindness! Risk of corneal clouding. Germ cell mutagenicity, Genotoxicity in vitro, Ames test, Salmonella typhimurium, Result: negative - Mutagenicity (mammal cell test): chromosome aberration, Result: negative - Teratogenicity, Did not show teratogenic effects in animal experiments .

Metabolism, toxicokinetics, mechanism of action and other information

## MI554AU-0 - Tartaric Acid Reagent A (test vial)

## 11. Toxicological information ... / >>

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

#### ACUTE TOXICITY

ACETIC ACID LD50 (Oral) LD50 (Dermal) LC50 (Inhalation)

3310 mg/kg Rat 1060 mg/kg Rabbit 11.4 mg/l/4h Rat

#### SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

#### RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

### REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

## 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

#### 12.1. Toxicity

ACETIC ACID

ACETIC ACID 100%: Toxicity to algae, IC5 Scenedesmus quadricauda (Green algae): 4,000 mg/l, 16 h, (maximum permissible toxic concentration) (Lit.) - Toxicity to bacteria, EC5 Pseudomonas putida: 2,850 mg/l, 16 h, neutral (maximum permissible toxic concentration) (Lit.), microtox test EC50 Photobacterium phosphoreum: 11 mg/l, 15 min.

MI554AU-0 - Tartaric Acid Reagent A (test vial)

## 12. Ecological information ... / >>

ACETIC ACID	
LC50 - for Fish	> 300.8 mg/l/96h Oncorhynchus mykiss
EC50 - for Crustacea	> 300.82 mg/l/48h Daphnia magna
12.2. Persistence and degradability	
ACETIC ACID ACETIC ACID 100%: Biodegradability 99 %, 30 d, R Demand (BOD) 880 mg/g (5 d) - Ratio BOD/ThBOD	Readily biodegradable - 95 %; 5 d, Readily eliminated from water - Biochemical Oxygen BOD5 76 %.
ACETIC ACID	
Solubility in water Rapidly degradable	> 10000 mg/l
12.3. Bioaccumulative potential	
ACETIC ACID	
Partition coefficient: n-octanol/water	-0.17
12.4. Mobility in soil	
ACETIC ACID	
Partition coefficient: soil/water	1.153
12.5. Results of PBT and vPvB assessment	
On the basis of available data, the product does not	contain any PBT or vPvB in percentage greater than 0,1%.
12.6. Other adverse effects	

ACETIC ACID

ACETIC ACID 100%: Biological effects, Harmful effect due to pH shift. Caustic even in diluted form. Discharge into the environment must be avoided.

## 13. Disposal considerations

### 13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste. Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. CONTAMINATED PACKAGING Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

## 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number

Not applicable 14.2. UN proper shipping name

Not applicable 14.3. Transport hazard class(es)

Not applicable 14.4. Packing group

Not applicable

## 14. Transport information ... / >>

## 14.5. Environmental hazards

Not applicable 14.6. Special precautions for user

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

## 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

U.S. Federal Regulations

Clean Air Act Section 112(b): No component(s) listed.

Clean Air Act Section 602 Class I Substances: No component(s) listed.

Clean Air Act Section 602 Class II Substances: No component(s) listed.

Clean Water Act – Priority Pollutants: No component(s) listed.

Clean Water Act – Toxic Pollutants: No component(s) listed.

DEA List I Chemicals (Precursor Chemicals): No component(s) listed.

DEA List II Chemicals (Essential Chemicals): No component(s) listed.

EPA List of Lists: 313 Category Code: No component(s) listed.

EPCRA 302 EHS TPQ: No component(s) listed.

EPCRA 304 EHS RQ: No component(s) listed.

CERCLA RQ: 64-19-7 ACETIC ACID

EPCRA 313 TRI: No component(s) listed.

RCRA Code: No component(s) listed.

CAA 112 (r) RMP TQ: No component(s) listed.

State Regulations

Massachussetts: 64-19-7 ACETIC ACID

Minnesota:

MI554AU-0 - Tartaric Acid Reagent A (test vial)

## 15. Regulatory information ... / >>

64-19-7	ACETIC ACID
New Jersey:	ACETIC ACID
New York: 64-19-7	ACETIC ACID
Pennsylvania: 64-19-7	ACETIC ACID
California:	

64-19-7 ACETIC ACID

### Proposition 65:

This product does not contain any substances know to the State of California to cause cancer, reproductive harm or birth defects.

#### International Regulations

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

#### None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention: None

Candadian WHMIS Information not available

## 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

H226	Flammable liquid and vapour.
H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H315	Causes skin irritation.

LEGEND:

- 313 CATEGORY CODE: Emergency Planning and Community Right-to Know Act Section 313 Category Code
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAA 112 ® RMP TQ: Risk Management Plan Threshold Quantity (Clean Air Act Section 112®)
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CERCLA RQ: Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)
- CLP: EC Regulation 1272/2008
- DEA: Drug Enforcement Administration
- EmS: Emergency Schedule
- EPA: US Environmental Protection Agency
- EPCRA: Emergency Planning and Community Right-to Know Act
- EPCRA 302 EHS TPQ: Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code)
- EPCRA 304 EHS RQ: Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)
- EPCRA 313 TRI: Toxics Release Inventory (Section 313 Category Code)
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PEL: Predicted exposure level
- RCRA Code: Resource Conservation and Recovery Act Code
- REL: Recommended exposure limit
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.

## MI554AU-0 - Tartaric Acid Reagent A (test vial)

## 16. Other information ... / >>

- TSCA: Toxic Substances Control Act- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- WHMIS: Workplace Hazardous Materials Information System.

GENERAL BIBLIOGRAPHY:

- GHS rev. 3
- The Merck Index. 10th Edition
- Handling Chemical Safety
- Niosh Registry of Toxic Effects of Chemical Substances
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy
- 6 NYCRR part 597
- Cal/OSHA website
- California Safe Drinking Water and Toxic Enforcement Act
- EPA website
- Hazard Comunication Standard (HCS 2012)
- IARC website
- List Of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112® of the Clean Air Act
- Massachussetts 105 CMR Department of public health 670.000: "Right to Know"
- Minensota Chapter 5206 Departemnt Of Labor and Industry Hazardous Substances, Employee "Right to Know".
- New Jersey Worker and Community Right to know Act N.J.S.A.
- NTP. 2011. Report on Carcinogens, 12th Edition.
- OSHA website
- Pennsylvania, Hazardous Substance List, Chapter 323

#### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses. Provide appointed staff with adequate training on how to use chemical products.

Product's classification is based on the criteria set out in OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200), unless otherwise indicated in sections 11 and 12.

The data for evaluation of chemical-physical properties are reported in section 9.

Changes to previous review: The following sections were modified: 01 / 03 / 04 / 05 / 08 / 09 / 10 / 11 / 12. ΕN